

Vizufon

Based on **C&S**

CIP-2 Series



- ✓ ***Vivid video display***
- ✓ ***International IP Telephony Standards***
- ✓ ***User Friendly Graphic User Interface***
- ✓ ***Various Application Supportable Features***
- ✓ ***Flexible Remote Maintenance Methods***
- ✓ ***All in one Solution : Chip to Applications***
- ✓ ***Inter-operability with most IP Telephony Equipment***
- ✓ ***Cost-effective Video over IP Phone***

- System Protocol
 - ITU-T Recommendation H.323 Ver. 3.0
 - IETF Recommendation SIP RFC 3261
- Network
 - 10 / 100 Base-T
 - Integrated Hub Function (2 RJ-45 Ports) : CIP-5700 Only
 - Support LAN, ADSL, CABLE MODEM
 - Support PPP/PPPoE
- Video
 - ITU-T Recommendation : H.263
 - CIF Resolution : 352 x 288 pixels
 - QCIF Resolution : 176 x 144 pixels
 - Maximum Frame rate (CIF) : 30 fps
- Audio
 - ITU-T Recommendation : G.723.1/711
 - Frequency response : 50Hz ~ 3.4KHz
 - Full Duplex
- Camera
 - 1/3" Built-in CMOS Camera
 - Auto exposure / white balance
- Display
 - 2.5" diagonal active matrix TFT LCD
 - Resolution : 480 x 234 pixel
- E-mail(optional)
 - Send/Receive E-mails
 - Send/Receive SMS(Short Message Service)
 - POP3, SMTP
- Web Browser(optional)
 - Browse Web Sites and Contents with a built-in cHTML Browser
- GUI
 - User friendly Graphic User Interface
- Internet Protocols
 - TCP/IP, UDP, ICMP, DHCP
- Electrical
 - Power Consumption (max) : 17W
 - Power Supply (AC Adaptor) : 110 ~ 240 AC
 - Operation Voltage : +5V DC
- Voice Encryption(optional)
 - ITU-T Recommendation : H.235
 - Security framework used to provide authentication, encryption and integrity to H.323 systems
- Etc.
 - NAT(Max. 2.5 Mbps)
 - H.450 support(optional)
 - 1 RJ-11 port for PSTN (Optional)
 - Remote Upgrade(TFTP)
 - Maintenance Support(Optional) : SNMP, Embedded Web Server



CIP-2500



CIP-5700

